

Duo-Flex Plunger



**FERGUSON
BEAUREGARD™**
New Intelligence In Problem Solving™



Application

For use in gas wells and high-ratio oil wells where greater sealing efficiency is needed.

Features

Two sets of Mini-flex seals (16 interlocking pads) offer greater sealing capability. Available with bypass and in special materials where CO₂ or H₂S is present.

Benefits/Advantages

The Duo-Flex is able to travel with less pressure and with less gas slippage. Often used with an internal bypass, allowing it to fall faster in liquids.

New intelligence in problem solving™

The Duo-Flex Plunger is another low-cost, efficient method of increasing and optimizing production in oil and gas wells that have marginal flow characteristics.



Features:

- Sixteen interlocking stainless steel pads
- "Flex" pads
- Available with or without a bypass system
- Superior seal for weaker wells

Technical Specifications

Size	1¼	1½	2¼	2¾	2⅞	3
Part #	—	—	—	PIG20T10	PIG25T10	PIG30T10
Overall Length	—	—	—	16.215"	16.215"	16.215"
O.D. (Max.)	—	—	—	2.000"	2.450"	2.936"
O.D. (Min.)	—	—	—	1.850"	2.250"	2.750"
Fishing Neck Size	—	—	—	1¾"	1¾"	1¾"
Weight	—	—	—	9.88 lbs.	14.6 lbs.	17.4 lbs.

Contact us today to learn how Plunger Lift Technology can help improve your production performance. Visit our web site—or email us at: Automation@FergusonBeauregard.com

P.O. Box 130158

Tyler, TX 75713

(903) 561-4851

fax (903) 561-6567

www.FergusonBeauregard.com