

Barstock Cleanout Plunger



**FERGUSON
BEAUREGARD™**
New Intelligence In Problem Solving™



Application

Ideal for wells with high gas to liquid ratios, wells making small amounts of sand or wells with tight spots.

Features

One piece solid design makes plunger both durable and economical. Deep external grooves trap gas to help create seal. Rounded edges on grooves allow plunger to pass through some tight spots that might hang plungers with sharp edges. Slightly smaller O.D. than conventional barstock plungers.

Benefits/Advantages

This plunger has grooves machined on the outer surface to create a “turbulent” seal. Plunger is shorter than most barstock plungers which helps it pass through tight spots or slight bends. Plunger has minimal wear tendencies.

New intelligence in problem solving™

The Barstock Cleanout Plunger is another low-cost, efficient method of increasing and optimizing production in oil and gas wells that have marginal flow characteristics.



Features:

- External Grooves create “turbulent” seal
- Excellent for wells with high gas/liquid ratio
- Economical and low maintenance
- Available in a variety of O.D.'s

Technical Specifications

Size	1¼	1½	2¼	2¾	2⅞	3½
Part #	—	PIG15CD10	PIG21CD10	PIG20CD10	PIG25CD10	—
Overall Length	—	14.000"	14.000"	14.000"	14.000"	—
O.D. (Max.)	—	1.470"	1.610"	1.870"	2.330"	—
O.D. (Min.)	—	—	—	—	—	—
Fishing Neck Size	—	1.188"	1.188"	1.375"	1.375"	—
Weight	—	4.2 lbs.	5.5 lbs.	7.3 lbs.	11.3 lbs.	—

Contact us today to learn how Plunger Lift Technology can help improve your production performance. Visit our web site—or email us at: Automation@FergusonBeauregard.com

P.O. Box 130158

Tyler, TX 75713

(903) 561-4851

fax (903) 561-6567

www.FergusonBeauregard.com