



Application

One of a family of pad plungers, the Mini-Flex is applicable for use in most plunger-lift wells.

Features

With eight interlocking stainless steel pads, the Mini-Flex creates an efficient seal. The spring-loaded pads are always expanded, yet have enough flex to allow the plunger to fall through minor tubing size anomalies.

Benefits/Advantages

The Mini-Flex, the work-horse of the plunger industry, is small, lightweight and simple. This widely imitated design has become an industry standard.

New intelligence in problem solving™

The Mini-Flex Plunger is another low-efficient method of increasing and optimizing production in oil and gas wells that have marginal flow characteristics.

Features:

- Eight interlocking stainless steel pads
- “Flex” design
- Efficient and simple
- Versatile and attractively priced



Technical Specifications

Size	1¼	1½	2¼	2¾	2⅞	3½
Part #	—	—	—	PIG20A10	PIG25A10	—
Overall Length	—	—	—	9.834"	10.441"	—
O.D. (Max.)	—	—	—	2.000"	2.465"	—
O.D. (Min.)	—	—	—	1.850"	2.250"	—
Fishing Neck Size	—	—	—	13/8"	13/8"	—
Weight	—	—	—	5.5 lbs.	10 lbs.	—

Contact us today to learn how Plunger Lift Technology can help improve your production performance. Visit our web site—or email us at: Automation@FergusonBeauregard.com

P.O. Box 130158

Tyler, TX 75713

(903) 561-4851

fax (903) 561-6567

www.FergusonBeauregard.com