

Continuous Flow Beau-Flex Plunger



**FERGUSON
BEAUREGARD™**
New Intelligence In Problem Solving™



Application

Ideal for deeper wells that require less shut-in time but still need excellent sealing efficiency.

Features

Contains eight interlocking stainless steel pads that expand to a diameter greater than the inside diameter of the well tubing. Unique, newly designed valve and seal system.

Benefits/Advantages

This model requires less shut-in time than conventional plungers allowing you to increase the fall-rate. The newly designed seal system further eliminates gas slippage making wells more productive.

New intelligence in problem solving™

The Continuous Flow Beau-Flex is another low cost, efficient method of increasing and optimizing production in oil and gas wells that have marginal flow characteristics.

Features:

- Excellent sealing characteristics
- Advanced seal system
- Unique Valve Design
- Delivers maximum efficiency
- Maintains its "flex" design



Technical Specifications

Size	1¼	1½	21/16	23/8	27/8	3
Part #	—	—	—	PIG20BF30	PIG25BF30	—
Overall Length	—	—	—	15.078"	15.662"	—
O.D. (Max.)	—	—	—	2.025"	2.490"	—
O.D. (Min.)	—	—	—	1.875"	2.320"	—
Fishing Neck Size	—	—	—	13/8"	13/8"	—
Weight	—	—	—	8.7 lbs.	13.3 lbs.	—

Contact us today to learn how Plunger Lift Technology can help improve your production performance. Visit our web site or email us at: staff@fbdoover.com

P.O. Box 130158

Tyler, TX 75713

(903) 561-4851

fax (903) 561-6567

www.fbdoover.com