



Application

Ideal for weaker wells where plunger performance is marginal or where plungers have not previously proven successful.

Features

Contains eight interlocking stainless steel pads that expand to a diameter greater than the inside diameter of the well tubing. Advanced seal system eliminates gas slippage. Our best sealing plunger.

Benefits/Advantages

In wells where plunger performance is marginal, this model can increase production. The Ultraflex can work in wells where there is insufficient gas pressure to operate other plungers.

New intelligence in problem solving™

The Ultraflex Plunger is another low-cost, efficient method of increasing and optimizing production in oil and gas wells that have marginal flow characteristics.



Features:

- Excellent sealing characteristics
- Advanced seal system
- Works where other plungers fail
- Delivers maximum efficiency
- Maintains its "flex" design

Technical Specifications

Size	1¼	1½	2¼	2¾	2⅞	3½
Part #	—	PIG15SS10	PIG21SS10	PIG20SS10	PIG25SS10	PIG30SS10
Overall Length	—	10.858"	8.919"	11.400"	12.600"	12.920"
O.D. (Max.)	—	1.640"	1.775"	2.025"	2.490"	3.020"
O.D. (Min.)	—	1.500"	1.625"	1.875"	2.325"	2.875"
Fishing Neck Size	—	13/16"	13/16"	13/8"	13/8"	13/8"
Weight	—	4.5 lbs.	4 lbs.	7 lbs.	11.6 lbs.	17.5 lbs.

Contact us today to learn how Plunger Lift Technology can help improve your production performance. Visit our web site—or email us at: Automation@FergusonBeauregard.com

P.O. Box 130158

Tyler, TX 75713

(903) 561-4851

fax (903) 561-6567

www.FergusonBeauregard.com